



► Feature:

1. Aluminum grille, rust-proof box
2. UL94V-0 flame retardant grade material (optional)
3. 4x3 inch high performance ferrite driver unit
4. UV waterproof dipping paint, IPx4 waterproof level, can be installed indoors and outdoors (optional)
5. Optional intelligent installation accessories, including level device, quick-release handle device, and anti-shock rubber pad
6. The array sound column speaker adopts a streamlined design, beautiful and practical appearance, suitable for sound reinforcement in various architectural spaces, and the sound quality is beautiful and pleasant.
7. The sound column speaker adopts ABS plastic mixed glass fiber reinforced box, which is strong and durable.
8. The circular waveguide hole in the front and the damping port at the rear of the box form a unique low-frequency heart-shaped diffusion. The treble is crisp and pleasant, the tone is natural and thick, and the bass is full.

► Specification:

Drive unit	4x3" ferrite
Cone material	pulp coating
Impedance	8Ω
Rated power	100W (400W, PEAK)
SPL (1W/1m)	95dB
Maximum SPL (1W/1m)	115dB
Frequency response	150Hz~14kHz, -6dB 80Hz~20kHz, -10dB
Shell material	ABS plastic + fiberglass
Grille material	aluminum
Diffusion angle (-6dB)	vertical >20°, horizontal >120°
Connection interface	red and black crimping clamp
Mounting holes	10 M6
Installation system	intelligent mounting bracket/embedded mounting bracket
Color	black/white (optional)
Dimensions (height × width × depth)	530x100x150mm
Product net weight	3.80kg
Packing weight	5.08kg