



### Feature:

1. Top-grade gold film high-fidelity microphone capsule, super-directional radio effect, better sound quality
2. Connect the microphone to the 48V microphone preamplifier power supply component
3. The effective pickup angle of 100° can prevent interference from adjacent microphones and suppress howling.
4. Low impedance balanced audio output
5. Microphone adjustable elevation angle -50° to 45° (horizontal)
6. Made of zinc/aluminum alloy material, anodized process, CNC precision processing high-gloss edge, novel appearance, simple and elegant
7. The microphone panel can be customized with silk screen or laser LOGO/pattern

### Specification:

Pickup microphone	14mm diameter gold-plated condenser microphone
Directional characteristics	supercardioid
Sensitivity	-28 dB
Frequency response	30Hz-18KHz
Output impedance	<200Ω
Maximum sound pressure level	130 dB (THD<3%)
Signal-to-noise ratio	> 74 dB
Total harmonic distortion	<0.05%
Equivalent noise	25 dB-A
Dynamic range	>108 dB (1 KHz)
Phantom power	48V DC
Maximum power consumption	0.3W
Shell material	zinc/aluminum alloy
Connection method	audio cable - 2 cores shielded
Weight	1kg
Color	Grey
Dimensions (mm)	length*width*height, Microphone pole: 200*34.5*23, base: 138*98*54