



Feature:

1. The overall appearance is high-end and solemn, with beautiful appearance design and in line with modern aesthetic standards.
2. Professional high-fidelity capacitor 14mm microphone core, sensitive pickup and clear voice.
3. Anti-interference circuit design can prevent interference from electronic products such as mobile phones.
4. The microphone stem has a speaking indicator light (it does not light up when you are not speaking, and lights up red when you are speaking), which displays the speaking or off status of the unit.
5. The speaking button has an indicator light that lights up blue when speaking and red when not speaking.
6. The unit is a passive device, powered by the system host, and the voltage is DC24V, which is within the safe range.
7. The 2.4-inch TFT color LCD can display the chairman' s identity, ID number, time, speech timing and other information.
8. The chairman unit can be installed arbitrarily without being restricted by location when connected, and has the priority function of fully controlling the meeting order.
9. Hand-in-hand connection mode for easy installation and maintenance.

Specification:

Frequency range	640-690MHz	Modulation method	wideband FM
Number of channels	200 channels	Receiving mode	Diversity receiving CPU automatically selects the strongest signal channel
Frequency bandwidth	50MHz	Sensitivity	Sensitivity
Frequency stability	±0.001%	Dynamic range	>90dB
Peak frequency deviation	±45KHz	Frequency response	50Hz-18KHz (±3dB)
Comprehensive signal-to-noise ratio	>85dB	Comprehensive distortion	Comprehensive distortion
Operating distance	80 meters	Frequency binding method	infrared + wireless
Audio output	mixed:0-600mV, balanced:0-600mV	Power supply	DC 12V 2A
Transmission power	10mW	Maximum number of channels	200
Spurious suppression	-60dB	Harmonic suppression	>55dBc
Power supply voltage	4.2V/3000mAh lithium battery	Screen	2.4-inch TFT color screen
Working time	speaking mode > 16 hours, standby mode >30 hours	Microphone tube length	220mm short square tube