



Feature:

1. Using digital technology as the core and built-in high-performance CPU
2. The audio signal is processed by 32bit high-speed floating point DSP, with perfect clear sound quality of 20Hz~20KHz.
3. High-performance switching power supply reduces any impact on sound quality due to long-distance transmission
4. Anti-interference circuit design to prevent interference from mobile phone signals
5. Supports chairman-only mode, fully open mode, first-in-first-out mode, and restricted mode
6. You can choose SONY-RS232/RS422/PELCO-D to control the camera
7. Multiple audio input and output interfaces, which can be connected to sound reinforcement or recording equipment
8. It has a central control code RS-232 interface and can be connected to the central control system.

Specification:

| | |
|---------------------------------|---|
| Host power supply | AC110V-220V/50Hz |
| Frequency response | 20HZ-20kHz |
| Signal-to-noise ratio | =96dBA |
| Total harmonic distortion | ≤0.05% |
| Microphone unit interface | round head DIN-8 socket interface × 2, RJ45 network |
| Line interface | ×4 |
| Central control connection port | 232 serial port × 1 |
| Camera interface | RS-232 small serial port × 1 |
| Camera interface | RS-422 serial port × 1 |
| Video matrix interface | DB9/9 pin male |
| Audio input | RCA (Lotus socket) x1 |
| Audio output | RCA (Lotus socket) x1 XLR XLR socket x1 |
| External dimensions (LXWXH) | 483×323×90mm |
| Color | grey |