



► Feature:

1. The overall appearance is high-end and solemn, with beautiful appearance design and in line with modern aesthetic standards.
2. Professional high-fidelity capacitor 14mm microphone core, sensitive pickup and clear voice.
3. Anti-interference circuit design can prevent interference from electronic products such as mobile phones.
4. The microphone stem has a speaking indicator light (it does not light up when you are not speaking, and lights up red when you are speaking), which displays the speaking or off status of the unit.
5. The speaking button has an indicator light that lights up blue when speaking and red when not speaking.
6. The unit is a passive device, powered by the system host, and the voltage is DC24V, which is within the safe range.
7. The 2.4-inch TFT color LCD can display the chairman's identity, ID number, time, speech timing and other information.
8. The chairman unit can be installed arbitrarily without being restricted by location when connected, and has the priority function of fully controlling the meeting order.
9. Hand-in-hand connection mode for easy installation and maintenance.

► Specification:

Frequency response	20Hz-20KHz
Total harmonic distortion	<0.05%
Sensitivity	-46 dBV/Pa
Signal-to-noise ratio	>80dB
Channel crosstalk	>80dB
Equivalent noise	20 dBA (SPL)
Maximum sound pressure level	125 dB (THD<3%)
Input impedance	2 kΩ
Display	2.4-inch tft color display; resolution 240x320
Directivity	cardioid
Output wiring	comes with 1.1m eight-core female connector
Base size	100 width × 134 depth × 57 height mm (excluding shaft)
Microphone pole size	220 length × 33 width × 25 height mm