



### Feature:

1. 2.4-inch TFT color LCD display, which can display channel, power, chairman's identity, address ID number, speech timing, etc.
2. The unit uses 3600mAH lithium-ion battery, which has ultra-low power consumption and can work continuously for 8 hours and has a standby time of up to 12 hours.
3. Long press the speak button to enter the unit settings, and modify the unit's channel, address ID number and other settings.
4. Humanized functions, high-definition vocal restoration, unique battery life and power supply, and rejection of interference.
5. The microphone stem has an indicator light (it does not light up when you are not speaking, and it lights up in red when you are speaking), and a speaking button (it does not light up when you are not speaking, and it lights up in red when you are speaking).
6. Built-in Type-C charging interface.

### Specification:

|                        |  |
|------------------------|--|
| Carrier frequency band | UHF640MHz-690MHz                                     |
| Oscillation mode       | PLL phase locked frequency synthesis                 |
| Harmonic radiation     | < -65dBm   |
| Bandwidth              | 50MHz  |
| Maximum offset         | ±45KHz   |
| Microphone core        | condenser 14mm microphone core, cardioid directivity |
| Battery used           | 3600mAH lithium-ion battery                          |
| Current consumption    | <200mA   |
| Microphone rod size    | length 360mm, microphone head diameter 26mm          |
| Base size              | width 100*depth 134*height 57mm                      |