



Feature:

1. Top-grade gold film high-fidelity microphone capsule, super-directional radio effect, better sound quality
2. Built-in high-performance CPU, faster processing speed and better sound quality
3. The effective pickup angle of 100° can prevent interference from adjacent microphones and suppress howling.
4. Cooperate with the video switcher and camera, and use the computer preset to realize the automatic tracking function of the camera
5. Customized chairman machine configuration function, any unit can be temporarily defined as a chairman unit according to on-site needs, and there is no limit on the number of chairman units
6. Microphone adjustable elevation angle -50° to 45° (horizontal)
7. The system has automatic repair function and supports "hot plugging" of lines.

Specification:

Output frequency response	40Hz-16KHz
Signal-to-noise ratio	>74 dB
Dynamic range	>108 dB (1 KHz)
Total harmonic distortion	<0.05%
Maximum power consumption	1.5W
Headphone volume	10mW
Headphone load	>16 Ω
Headphone output interface	Ø 3.5 mm stereo jack
Color	Grey
Shell material	zinc/aluminum alloy
Weight	0.9kg
Connection method	FionTu conference six-core dedicated cable
Dimensions (mm)	Microphone pole: 200*34.5*23, base: 138*98*54
Pickup microphone	14mm diameter gold-plated condenser microphone
Directional characteristics	Supercardioid
Sensitivity	28 dB
Frequency response	30Hz-18KHz
Input impedance	2.2K Ω
Maximum sound pressure level	130 dB (THD<3%)
Equivalent noise	25 dB-A